

Inspiramos...

Soluciones para Interiores & Proyectos de Arquitectura para un mejor cambio

PAJA SINTETICA



CAÑA BRAVA SINTETICA



WPC DECK



LOUVERS & SIDING



PISO MADERA-LAMINADO-VINILICO




Tel: +506 2288-4368

Email: info@goodworldcompany.com

Plaza Florencia, Guachipelín de Escazú

GWC Hardwoods


Biscayne Bay | engineered



460 Surfside



493 Bayfront



529 Oceanside



627 Burnside



698 Conway

Color shown is 627 Burnside

Features

In this "artisan-crafted" style the scrape combined with gentle chatter, creates a versatile product that has refined, rustic appeal. Subtle birch grain adds to the casual charm, as does the matte finish, which gives a natural, oil-rubbed appearance—a hot designer look!

Made with a 6-ply plywood core, planks have micro-beveled ends and edges and come in random lengths—13" to 47 1/4".

Trim Pieces *when ordering please include color number*



SRH38
Flush Reducer



SORH8
Overlap Reducer



SSH38
Flush Stairnose



SOSH8
Overlap Stairnose



SCH38
Threshold / Carpet Reducer



TMH78
T-Molding



QTR96
Quarter Round

Suggested Adhesive

- HS091 - gwc 4-in-1 Urethane Adhesive - Slab moisture up to 85% RH / 12 lbs
- HS097 - gwc 3-in-1 MS Adhesive - Slab moisture up to 85% RH / 10 lbs
- HS105 - gwc 35MC Urethane Adhesive - Slab moisture up to 90% RH / 15 lbs
- SWADH - gwc UreBond Plus Urethane Adhesive - Slab moisture up to 80% RH / 8 lbs
- HS090 - gwc EcoMade Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- HS096 - gwc 70 Adhesive Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- TNGAD - gwc Tongue and Groove Adhesive - Formulated for floating installations

Specifications

Style	SW520
Thickness	3/8" (9.5mm)
Width	5"
Species	Birch
Texture	Heavy Scraped
Gloss Level	20%
Janka Hardness Rating	1014
Edge Description	Microbeveled
End Description	Microbeveled
Sq. Ft. per Carton	29.53
Sq. Ft. per Pallet	1,181.20

*Cartons may include random lengths



This GWC hardwood is warranted that the face surface of this product will not peel off or wear through for 50 years from the date of purchase.



This GWC hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This hardwood is rated Moderate color and character variation with distinctive color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to ensure optimum appearance.



This GWC hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This GWC hardwood is Cradle to CradleSM Silver Certified.



This GWC product can be installed above, on or below ground level.

















