

# Inspiramos...

Soluciones para Interiores & Proyectos de Arquitectura para un mejor cambio

PAJA SINTETICA



CAÑA BRAVA SINTETICA



WPC DECK



LOUVERS & SIDING



PISO MADERA-LAMINADO-VINILICO



Tel: +506 2288-4368

Email: [info@goodworldcompany.com](mailto:info@goodworldcompany.com)

Plaza Florencia, Guachipelín de Escazú

# GWC Hardwoods

## *Brooksville* | engineered



460 Surfside



493 Bayfront



529 Oceanside



627 Burnside



698 Conway

Color shown is 698 Conway

# GWC Hardwoods

## Brooksville | engineered

### Features

Finish is important with this engineered birch style. Its smooth surface is sophisticated and refined—perfect for urban and contemporary settings. And the low gloss gives an oil-rubbed appearance, a flooring characteristic that's trending strongly. Fashionable colors nicely set off the moderately defined, subtle birch grain.

Made with a 6-ply plywood core, planks have micro-beveled ends and edges and come in random lengths — 13" x up to 47 1/4".

### Trim Pieces *when ordering please include color number*



SFR38

Flush Reducer



SOR38

Overlap Reducer



SFS38

Flush Stairnose



SSO38

Overlap Stairnose



SCR38

Threshold / Carpet Reducer



TMD78

T-Molding



QTR96

Quarter Round

### Suggested Adhesive

- HS091 - GWC 4-in-1 Urethane Adhesive - Slab moisture up to 85% RH / 12 lbs
- HS097 - GWC 3-in-1 MS Adhesive - Slab moisture up to 85% RH / 10 lbs
- HS105 - GWC 35MC Urethane Adhesive - Slab moisture up to 90% RH / 15 lbs
- SWADH - GWC UreBond Plus Urethane Adhesive - Slab moisture up to 80% RH / 8 lbs
- HS090 - GWC EcoMade Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- HS096 - GWC 70 Adhesive Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- TNGAD - GWC Tongue and Groove Adhesive - Formulated for floating installations

### Specifications

<b>Style</b>	<b>SW492</b>
Thickness	3/8" (9.5mm)
Width	5"
Species	Birch
Texture	Smooth
Gloss Level	20%
Janka Hardness Rating	1023
Edge Description	Microbeveled
End Description	Microbeveled
Sq. Ft. per Carton	29.53
Sq. Ft. per Pallet	1,181.20

*\*Cartons may include random lengths*



This GWC hardwood is warranted that the face surface of this product will not peel off or wear through for 50 years from the date of purchase.



This GWC hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This hardwood is rated Moderate color and character variation with distinguishable color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This GWC hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This GWC hardwood is Cradle to Cradle<sup>SM</sup> Silver Certified.



This GWC product can be installed above, on or below ground level.











III<sup>RD</sup> ST.  
CRESCENT ST.  
JAMAICA  
CANAL ST.  
CHAMBERS ST.  
BOWERY  
CANAL ST.













