

Inspiramos...

Soluciones para Interiores & Proyectos de Arquitectura para un mejor cambio

PAJA SINTETICA



CAÑA BRAVA SINTETICA



WPC DECK



LOUVERS & SIDING



PISO MADERA-LAMINADO-VINILICO



Tel: +506 2288-4368

Email: info@goodworldcompany.com



Plaza Florencia, Guachipelín de Escazú

GWC

HARDWOOD ENGINEERED FLOORING



Color shown is 524 Tower



GWC

HARDWOOD ENGINEERED FLOORING

Features

The Castlewood collection has an abundance of the natural charm that makes wood floors so desirable. Creating its stunning character are stylish 7 1/2" widths, extremely handsome linear graining, and sawn face veneers that closely resemble solid hardwood.

Castlewood's two hickory colors and eight oak colors are visually rich—with the beautiful knots, mineral streaks, and natural splits seen in heirloom woods. Heightening its appeal is a very low-gloss finish, which calls to mind vintage European oil-rubbed floors.

Trim Pieces *when ordering please include color number*



SRH12
Flush Reducer



SORH2
Overlap Reducer



SSH12
Flush Stairnose



SOSH2
Overlap Stairnose



SCH12
Threshold / Carpet Reducer



TMH78
T-Molding



QTR96
Quarter Round

Suggested Adhesive

- HS091 - GWC 4-in-1 Urethane Adhesive - Slab moisture up to 85% RH / 12 lbs
- HS097 - GWC 3-in-1 MS Adhesive - Slab moisture up to 90% RH / 15 lbs
- HS105 - gwc 35MC Urethane Adhesive - Slab moisture up to 90% RH / 15 lbs
- SWADH - gwc UreBond Plus Urethane Adhesive - Slab moisture up to 80% RH / 8 lbs
- HS090 - GWC EcoMade Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- HS096 - gwc 70 Adhesive Resin Adhesive - Slab moisture up to 75%RH / 3 lbs
- TNGAD - GWC Tongue and Groove Adhesive - Formulated for floating installations

Specifications

Style	(Oak) SW485 (Hickory) SW486
Thickness	9/16" (14mm)
Width	7 1/2"
Species	(SW485) White Oak (SW486) Hickory
Texture	Wire Brush
Gloss Level	10%
Janka Hardness Rating	(oak) 1210 (hickory) 1926
Edge Description	Microbeveled
End Description	Microbeveled?
Sq. Ft. per Carton	31.09
Sq. Ft. per Pallet	1,243.60

*Cartons may include random lengths



This GWC hardwood is warranted that the finish of this product will not peel off or wear through for 50 years from the date of purchase.



This hardwood is rated High color and character variation with distinguishable and often extreme color variation within each box. It is imperative that hardwood planks from various cartons be continually blended during installation to ensure optimum appearance.



This GWC hardwood is approved for installation over water type radiant heated subfloors. Floating installation method only. Direct glue-down is NOT recommended!



This GWC hardwood meets the GREENGUARD indoor air quality requirements and is GREENGUARD Certified.



This GWC product can be installed above, on or below ground level.

GWC

HARDWOOD ENGINEERED FLOORING

Filled knots and splits are to be expected in this distinctive product. These are not defects and are considered acceptable additions to the rustic charm and character of these products. While these characteristics are to be expected, it is entirely possible to also receive extremely clean planks with little to no distinct character.





































